



# G-13

---

## COIN VALIDATOR



G-13

## Description

The NRI® G-13™ is the market leading 3.5" coin validator, setting the standards with its unique Multi-Frequency Technology (MFT) validation. This popular coin validator is highly flexible in its application range thanks to various models, interfaces, and sorters offered. Used in applications ranging from AWP and slot machines to carwash and laundry mats, the G-13 is well suited with anti-stringing protection and protocol encryption for high-manipulation security wherever it is needed.

CPI customers across the globe can attest to the resilience of this coin validator and its proven track record of being flexible in nature yet secure in validation.

## Benefits

---

**High security validator** uses unique Multi-Frequency Technology (MFT) protection against string manipulation and optical monitoring of the coin path

**Versatile interfaces and sorting options** make it appealing to a variety of applications.

**Flexible design and teach options** like inhibiting single or group coins/tokens, currency updates, and configuration uploads



COIN VALIDATOR

# Specifications

---

## Coin Insertion

- Single coin, top or front entry

## Coin Speed (coin/s)

- 2 - 6 Coins per second

## Dimensions (H x W x D in mm)

- Dimensions (HxWxD) 102mm x 89mm x 52mm

## Industry Format

- 3.5 inch

## Coin Sorting

- Optional / external 3-way

## Operating Temperature

- -25°C to +70°C

## Coin Processing

- 32 coins max. in 2 x 16 or 1 x 32 channels Coin Diameter: 15 – 31.5mm (optional up to 32.5mm) Coin Thickness: 1.5 – 2.5mm (optional up to 3.3mm)

## **Front Plate**

- Available for front entry

## **Interfaces Supported**

- Parallel: Standard version
- Parallel: SGI 16/49/46/62/33/80/100 versions as Simple Gaming Interfaces
- Parallel: Casino version for high-speed coin acceptance
- Parallel: AMU version for AWP Spain
- Parallel: With totalizer function as 1/2-price totalizer, Timer, TV totalizer
- Parallel: BDTA-compatible 16-pole interfaces
- Parallel: ECV-totalizer
- Serial: ccTalk, also in combination with USB
- Serial: MDB and S1

## **Supply Voltage**

- 10 V DC – 27 V DC  $\pm 10\%$ , Optional: 10 V DC – 48 V DC

## Variants



### Coin Entry and Outlet

- Top entry or front entry versions
- MIDI or MINI front plate
- Reversed coin outlet for top entry version

### Dimensions (mm)

- Dimensions (HxWxD) 50mm x 100mm x 200mm



### Wake-up Sensor for G-13.mft

#### For low power applications:

- Internal wake-up sensor
- Front plate with integrated wake-up sensor

### Dimensions (mm)

- Dimensions (HxWxD) 25mm x 150mm x 50mm

## Accessories



### Firmware Upload Tools (G-13)

- Mobile HENRI+ service tool for on-site uploads
- WinFlash2 PC application for back-office uploads



### Configuration Tools (G-13)

- Mobile HENRI+ service tool for on-site configuration uploads
- WinEMP PC application for back-office detail configuration
- WinEMP.dll program library for remote configuration uploads over host



### Test Tools (G-13)

- ccTalk Demo PC application for testing coin acceptance of G-13.mft ccTalk
- WinSPT PC application for testing coin acceptance and interfaces of serial G-13.mft



- i<sup>2</sup> Mini Hub
- USB/RS-232 adapters for G-13.mft ccTalk
- MDB converter
- Converter to connect a parallel G-13.mft to other payment system control boards
- a<sup>2</sup> long channel coin changer housing
- 5" housing
- Payment Manager program library for serial coin validators
- NRIHIDAPI.dll program library for serial coin validators



## Escrow

e<sup>2</sup> escrow for coin collection and deflection to cashbox or return area



## Sorters (G-13)

- s<sup>2</sup> SSD 3-way standard sorters
- s<sup>2</sup> HSD 3-way high-speed sorter with optional frame



## Front Plates for G-13.mft

- MIDI front plate (155 x 63mm)
- MINI front plate (120 x 60mm)





# COIN VALIDATOR



## ccTalk Demo PC Application (G-13)

For testing coin validation



## Manipulation Protection

Sensor for increased protection against manipulation in coin outlet area