



Transaction. Interaction. Convergence."



SPu90 Modular

Universal self-service payment solution

The SPu90 Modular is a versatile solution that enables fast payment with all card types at self-service and unattended points of sale.

Compact, hybrid reader

Manual for magnetic stripe and chip cards

Multiple communication options

Connects with a wide range of systems and networks

Contactless reader

Separate contactless module for optimum flexibility

Versatile payment solution

Can be used at all self-service points of sale

Modular design

Provides high flexibility for machine integration

Secure

Meets payment industries latest security standards

SPu90 Modular

The SPu90 Modular product suite provides a solution which facilitates unattended card payments including magnetic stripe, chip (EMV with or without PIN), and contactless (Visa payWave (incl. VOQOS), Mastercard® contactless, Expresspay, Discover D-PAS).

Compatible with all Visa and MasterCard transaction types including contactless, NFC, local and international e-purse, credit and debit card schemes.

Through the accompanying software development kit, local applications can be developed and certified easily, minimising time to market and launch costs.

The SPu90 offers a variety of configuration options and delivers a powerful combination of security, speed, reliability, and ease of integration. Of particular note is the wide range of communication interfaces which facilitate simple connection with vending machines, peripherals, hosts and wireless modem.

SPu90 Modular Evolution

The updated set of unattended products will retain all the features and benefits that have made the Spire Payments' Artema unattended solution so popular with integrators. In addition, new features include colour display, enhanced power management (for solar operation) and contactless support.

Using the same rugged physical and logical interfaces as the proven Spire Payments' Artema unattended solution, combined with the ability to run current software applications the SPu90 provides a simple migration and upgrade path for existing and new partners.

Based on Spire Payments' proven and easy-to-use inSPire™ development environment combined with the SP family security architecture and PKI, the unattended product suite is fully PCI PTS SRED compliant.

With options including contactless for all major schemes plus colour screen, the SPu90 will take self-service solutions to new heights.

SPu90H & SPu95H Hybrid MSR/Chip

Reader (Optional)

Smartcard/ Hybrid chip and magnetic stripe reader MSR reader (ISO 7816, ISO 7811, 3 tracks, T=0, T=1,

A, B, AB classes) • Anti-vandal metal bezel Shutter to prevent foreign body insertion Emergency power-fail card release

Remote pairing with SPu90P/C

Encryption and Support for SRED key management

Comms interfaces Up to 2 (SPu95H) or 5 SAMS (SPu90H) Physical interface Serial RS232 with power and "wake" signals

Certifications See Respective Datasheets

> Power 12V DC • Via RS232 port

Environmental -20 °C to +65 °C • 500,000 card insertion cycles

SPu90P PIN Pad & Display (Includes SPu90C)

Display Colour 2.8"TFT display (Landscape) • 240

x 320 pixels • Lens: Glass, Anti-Glare top

-Joire

surface, scratch resistant

Keyboard 16 keys with positive feedback

Anti-vandal metal front bezel and Keys • Housing

Marine Grade Stainless Steel

Protection Ingress IP65 (PIN Pad), Shock IK08 (PIN

CPU High performance 400MHz Secure ARM 11

128 MB NAND Flash, optional 256MB Memory

2MB NOR Flash for Bootloader 64MB SDRAM

Comms interfaces LAN-TCP/IP

Master/ Session & DUKPT Key Management • **Encryption and**

Support for SRED key management

PCI 4.x. EMV Compliant Certifications

4 x Serial interface ports allowing power, control Physical interfaces and wake in/out • 1 x USB OTG port • 1 x interfaces USB Device port • 1 x SAM connector • Ethernet LAN

10/100 port • Interface to external Contactless SC antenna module • Interface to Vending machines over MDB connector • Beeper piezo speaker multi frequency

Power 10V to 45V DC (peak) via MDB port

Dimensions Base – 143 mm (L) x 92 mm (W) x 44 mm (H)

Operation - 20°C to + 65°C. Storage - 20°C to + 70 °C Humidity 95% Maximum non-condensating (operating at 45°C) Environmental

SPu90R Contactless Reader (Optional)

Contactless interface • EMV • ISO 14443, 13.56MHz, Contactless reader

Type A/ Type B • Mifare, DESFire tags, NFC • 4 LEDs • Weather proof, UV rated plastic, Piezo beeper, multi

Interface 6 pin header, and SMA coax, 50cm interface cable to

SPu90P or C included

Dimensions 15 mm (L) x 75 mm (W) x 65 mm (H)

PCI PTS SRED 4 x compliant • EMV compliant Certifications

(for all SPu90 modules)

Ingress IP65, Shock IK08 Protection

Operation -20 °C to +65 °C • Storage -20 °C to +70 °C **Environmental**

Humidity 95% Maximum non-condensating

(operating at 45 °C)

SPu90C Controller

As per SPu90P with the exception of keyboard





28108 Alcobendas, Madrid

Tel: +34 917 227 700

Eastern Europe LLC

Tel: +7 4852 370234

UK Spire Payments Ltd

Milford Trading Estate Blakey Road , Salisbury

Fax: +44 (0)1722 430350

Dubai Spire Payments MEA (DMCC)

France Spire Payments France

92200 Neuilly-sur-Seine

Tel: +33 6 11 42 88 36

All information is subject to change without notice and Spire Payments does not warrant the information's accuracy or correctness. Spire Payments and the Spire Payments logo are trademarks, service marks or registered trademarks or service marks of Spire Payments Holdings S.à.r.l. All other trademarks are the property of their respective owners. Any Spire Payments software described in this document is subject to a Software Licence Agreement. Please refer to the Spire Software Licence Agreement for information regarding the terms of use.